LAW OFFICES

SUGHRUE, MION, ZINN, MACPEAK & SEAS, PLLC

2100 PENNSYLVANIA AVENUE, N.W. WASHINGTON, DC 20037-3213 TELEPHONE (202) 293-7060 FACSIMILE (202) 293-7860 www.sughrue.com

524 Rec'd PCT/PTO 2 4 NOV 1999

November 24, 1999



Assistant Commissioner for Patents Washington, D.C. 20231

PCT/DK99/00612 -filed November 9, 1999

Re:

Application of Jens Mourits SORENSEN, Ove Emil HANSEN, and Martin A.G. SCHOLTEN

A PROCESS FOR PRODUCING A SPRAY DRIED, AGGLOMERATED POWDER OF BABY FOOD, WHOLE MILK OR SKIM MILK, AND SUCH

POWDER

Our Ref: Q56941

Dear Sir:

The following documents and fees are submitted herewith in connection with the above application for the purpose of entering the National stage under 35 U.S.C. § 371 and in accordance with Chapter I of the Patent Cooperation Treaty:

- ☑ an executed Declaration and Power of Attorney.
- ☑ an English translation of the International Application.
- \square one (1) sheet of formal drawings.
- ☐ an English translation of Article 19 claim amendments.
- ☐ an English translation of Article 34 amendments (annexes to the IPER).
- ☑ an executed Assignment and PTO 1595 form.
- ☐ a Form PTO-1449 listing the ISR references, and a complete copy of each reference.
- ☑ a Preliminary Amendment

The Government filing fee is calculated as follows:

TOTAL FILING FEE	\$840.00
Recordation of Assignment	\$ 40.00
TOTAL FEE	\$880.00

BOX PCT

Assistant Commissioner for Patents Washington, D.C. 20231 Page Two November 24, 1999 PCT/DK99/00612 filed November 9, 1999

Checks for the statutory filing fee of \$840.00 and Assignment recordation fee of \$40.00 are attached. You are also directed and authorized to charge or credit any difference or overpayment to said Account. The Commissioner is hereby authorized to charge any fees under 37 C.F.R. §§ 1.16, 1.17 and 1.492 which may be required during the entire pendency of the application to Deposit Account No. 19-4880. A duplicate copy of this transmittal letter is attached.

There is no claim to priority.

Respectfully submitted,

SUGHRUE, MION, ZINN, MACPEAK & SEAS, PLLC 2100 Pennsylvania Avenue, N.W. Washington, D.C. 20037-3213 Telephone: (202) 293-7060

Facsimile: (202) 293-7860

Date: November 24, 1999

Neil B. Siegel

Registration No. 25,200

09/424393 488 Rec'd PCT/PTO 24 NOV 1999

PATENT APPLICATION

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

In re application of

Jens Mourits SORENSEN, et al.

Appln. No.: NEW PCT APPLICATION

Group Art Unit: Unassigned

Filed: November 24, 1999

Examiner: Unassigned

For: A PROCESS FOR PRODUCING A SPRAY DRIED, AGGLOMERATED POWDER OF

BABY FOOD, WHOLE MILK OR SKIM MILK, AND SUCH POWDER

PRELIMINARY AMENDMENT

Assistant Commissioner for Patents Washington, D.C. 20231

Sir:

Prior to examination, please amend the above-identified application as follows:

IN THE CLAIMS:

Please amend claim 3 as follows:

Claim 3,

line 1,

change "claims 1 or 2", to --claim 1--.

REMARKS

The filing of this Preliminary Amendment is to remove the multiple dependency of the above claim. Therefore, entry and consideration of this Amendment is respectfully requested.

Respectfully submitted,

Neil B. Siegel

Registration No. 25,200

SUGHRUE, MION, ZINN, MACPEAK & SEAS, PLLC 2100 Pennsylvania Avenue, N.W. Washington, D.C. 20037-3213

Telephone: (202) 293-7060 Facsimile: (202) 293-7860

Date: November 24, 1999

A process for producing a spray dried, agglomerated powder of baby food, whole-milk or skim-milk, and such powder.

5 Field of the invention

The present invention relates to spray drying of milk products, more specificly whole-milk, skim-milk and baby food products of the types termed infant formula and follow-up formula.

10

Background of the invention

Several processes are known for spray drying in which the resulting particles are agglomerated in the very spray drying step or in subsequent steps combined 15 therewith.

The present invention relates to the type of processes in which the liquid concentrates to be spray dried are atomized into a stream of hot drying gas in a spray drying chamber, and the particles formed thereby treated further in a fluidized bed maintained in the bottom portion of the drying chamber. The product recovered from said fluidized bed may be subjected to an after-treatment in a fluidized bed outside the drying chamber.

Drying (MSDTM), much more efficiently agglomerated powders can be obtained than in the prior "straight through" system having no fluidized bed in the drying chamber, i.a. because the existence of the fluidized bed in the bottom of the spray drying chamber permits higher average humidity also in the upper portion of the chamber and the system may be operated to have a substantial amount of fine particles blown off from the fluidized layer and reintroduced in the wet atomizer 35 cloud in the upper part of the chamber (EP 97484,

Niro). Furthermore, a certain agglomeration may take place in the fluidized bed itself and, with proper recycling of fines, in zones near the lower part of the chamber walls (EP 729383, Niro).

It is also assumed that in spray drying processes performed in drying chambers having rigid internal gas filters an agglomeration may take place between the particles settling on the filter surfaces (WO 97/14288, Niro).

10 In spite of the several possibilities existing for obtaining an agglomeration in connection with the spray drying process it has hitherto been mandatory to apply a certain re-wetting to obtain a product consisting of the desired large agglomerates. The term "re-wetting" is herein used in a somewhat broader sense than customary within the art of spray drying, and refers to a process in which solid particles are contacted with liquid droplets to create a very sticky surface of the particles hit by the droplets. While the particles are thus temporarily very sticky they adhere together to form large agglomerates which by drying form rather dense granules which only slowly disintegrate when

suspended in water.

Re-wetting with a view of increasing the degree of agglomeration may be performed as an after-treatment by spraying water or another liquid onto the powder in an external fluidized after-treatment bed, or it may be performed by introducing fine particle fractions into the drying chamber near the location for atomization of the feed liquid, whereby said particles are hit by the atomized droplets while these are still liquid as it is customary within the art, e.g. in the well-known "straight through" process. Also it is known to use a combination of these two measures as described, inter alia, in EP 0 705 062. Furthermore, it has been sug-

gested to spray water or feed liquid over the internal fluidized layer in the spraying chamber.

However, the use of re-wetting for agglomeration purposes has certain disadvantages.

In case the re-wetting is made not with a portion of the feed liquid to be dried but just with water, as it is customary, the process obviously has an increased energy consumption necessary for evaporating the extra water required for the re-wetting.

Within the dairy industries it has been recognized that the products of re-wetting processes may be inferior due to bacteriological contamination and also organoleptic qualities may be impaired.

The present inventors have also experienced that

when agglomerates are produced by processes involving
re-wetting in the hot atomizer zone, a special product
failure becomes important, when baby foods, whole-milk
or skim-milk powders to be re-constituted as drinkable
liquids for human consumption are produced. Said
failure, normally termed "grains", manifests itself as
very small lumps of powder visible on the walls of a
bottle or glass above the level of a liquid having been
agitated to disperse the agglomerated powder therein.

Although said grains may be of no importance from a nutritional point of view, a large amount of grains may by the consumer be regarded as an indication of inferior product quality, for which reason there is a substantial commercial interest in avoiding or reducing the amount of grains. However, the formation of grains in agglomeration processes recycling fine particles to the atomizer zone is regarded as unavoidable, and may set a maximum limit for the degree of agglomeration used in industrial production.

A further drawback of the prior art processes 35 involving re-wetting as an after-treatment for obtain-

ing or completing the desired agglomeration is the fact that the operation thereof requires skill and manpower, especially to avoid over-wetting and resulting product deterioration.

5

Summary of the invention

We have now found that it is possible to obtain a high-quality spray dried product of baby food, whole-milk or skim-milk, agglomerated to the desired extent 10 but showing less grains when reconstituted in water than usual for similarly agglomerated, commercial products. Also other product characteristics are improved, resulting in superior organoleptical properties.

The above desired qualities are obtained in a single drying apparatus, possibly followed by a conventional after-drying and cooling.

The invention is partly based on the recognition that improved qualities may be obtained by increasing 20 the proportion of agglomeration taking place on and along the inner surface of a part of the conical bottom section of a spray drying chamber, thereby substantially reducing the amount of fine particles being rewetted by contact with droplets in the atomizer zone in the drying chamber and removing the need for re-wetting the product in the internal or in an external fluidized bed.

Said increase of the proportion of agglomeration taking place on and along the conical bottom section is obtained by collecting fine particles on suitably placed internal filters, being flexible to enable particle release by a short counter blow of a moderate amount of pressurized air.

In the above cited WO 97/14288, Niro, internal 35 filters of rigid materials, e.g. sintered metal, are

disclosed. When fine particles collected on filters have to be efficiently released, it is necessary to apply a very strong counter blow, meaning that a substantial amount of the fine particles released 5 thereby is spread and dispersed into a large part of the chamber volume. In contrast thereto, particles may be released from the flexible filters by a smaller counter blow at lower pressure which does not spread the particles but allow them to fall directly down on 10 the conical section. The reason for this difference is that when particles have to be released from a rigid filter they are influenced directly of the counter blow air and carried away thereby, whereas each portion of a flexible filter itself receives a short movement or 15 dislocation by the impact of a short counter blow whereby release of particles is effected without spreading thereof.

Thus, the invention deals with a process for producing a spray dried baby food, whole-milk or skim-20 milk product in which process agglomeration is obtained with less simultaneous increase of the grains rate than usual. The process comprising the following steps:

atomizing a liquid concentrate of baby food, whole-milk or skim-milk as droplets centrally into the upper part of a drying chamber of which at least the lower portion is defined by a downward tapering frustoconical wall;

introducing drying gas at a temperature of 160-400° C downwards from the top of said chamber around 30 the atomized droplets to partially dry these to moist particles and carry them in a downward widering direction;

maintaining a fluidized particle bed at a temperature of 45-80° C in the bottom of the drying chamber 35 and/or in a lower extension thereof, by means of an

upward stream of fluidizing gas for drying, classifying and agglomeration of the particles therein;

withdrawing a stream of gas comprising spent drying gas introduced at the top of the chamber and gas from said fluidized bed and at a temperature of 60-95° C from the chamber through flexible filter elements within said chamber, thereby settling fine particles having been entrained by said stream on the surface of the filter elements;

releasing the fine particles settled on the flexible filter elements by short, moderate counter blows to cause them to fall down on the frusto-conical wall at a location at level with or above a horizontal ring-shaped area on said wall where the largest concentration of said moist particles would have reached said wall if no fine particles from the filter elements had fallen down thereon, from which location said fine particles slide downwards along the wall as a covering layer to reach said fluidized particle layer;

withdrawing an agglomerated product from the fluidized bed fulfilling one of the following three combinations of agglomerate size distribution and grains rate (dertermined by the method of analysis described herein):

25

- (i): D_{10} (< 10%): 50-100 μ m, D_{50} (< 50%): 150-225 μ m, D_{90} (< 90%): 350-450 μ m and grains = 1;
- (ii): D_{10} (< 10%): 100-200 μ m, D_{50} (< 50%): 225-30 400 μ m, D_{90} (< 90%): 450-600 μ m, and grains above 1 but below or equal to 2;
- (iii): D_{10} (< 10%): 200-300 μ m, D_{50} (< 50%): 400-600 μ m, D_{90} (< 90%): 600-900 μ m, and grains above 2 but below or equal to 3.

15

The percentages stated in connection with the size distribution limits are by weight.

The above-mentioned grain analysis has been developed by the present inventors and is performed as 5 follows:

Analysis method for grains

30 g of powder are added to 200 ml of 40° C water in a beaker. The mixture is stirred slowly for 20 seconds and then left for 5 minutes. The beaker is then tilted, so that the sides are moistened with solution and again placed in upright position. The amount of white spots left on the sides of the beaker is compared with standard photographs to give a rating from 1 (best) to 6.

The present process enables manufacture of products comprising very large agglomerates without having a higher content of grains than found in presently marketed less agglomerated products. Alternatively, products may be manufactured being only moderately agglomerated but containing extremely few grains.

In the present process the produced particles and agglomerates are subjected to substantially less physical handling than in prior art processes involving external separation of fine particles having been entrained in the spent drying gas and recycling thereof to the chamber. This is also one of the reasons why a superior product is obtained.

The invention also comprises an agglomerated spray dried whole or skim-milk or baby food prepared by the defined process and fulfilling one of the following three combinations of agglomerate size distribution and grains rate:

- (i): D_{10} (< 10%): 50-100 μ m, D_{50} (< 50%): 150-225 μ m, D_{90} (< 90%): 350-450 μ m and grains = 1;
- (ii): D_{10} (< 10%): 100-200 μ m, D_{50} (< 50%): 225-400 μ m, D_{90} (< 90%): 450-600 μ m, and grains: above 1 but below or equal to 2;
- (iii): D_{10} (< 10%): 200-300 μ m, D_{50} (< 50%): 400-600 μ m, D_{90} (< 90%): 600-900 μ m, and grains: above 2 but below or equal 3.

It is believed that a spray dried whole-milk, skim-milk or baby food presenting the combination of agglomeration size distribution and low content of grains specified under (ii) and (iii) above is a novel product, and thus a further feature of the invention is the provision of the products defined in the claims 5 and 6.

The invention is further described with reference 20 to the drawing.

Brief description of the drawing

In the drawing the sole figure very schematically shows a section through a spray drying apparatus with gas, droplets and particle flow indicated to illustrate the process of the invention.

Detailed description of the invention

In the drawing a drying chamber is defined by an upper cylindrical wall 1 and a lower frusto-conical wall 2. Liquid feed in the form of a concentrate of baby food, whole-milk or skim-milk is provided through conduit 3 and by means of an atomizer 4 injected as droplets into the drying chamber.

The atomizer 4 may be of any conventional construction, such as a rotary atomizer wheel, a 2-fluid nozzle or a pressure nozzle. Preferably, it is a pressure nozzle ejecting the atomized droplets in a path forming a hollow wide cone.

For the sake of simplicity, only one atomizer is shown in the drawing. In industrial production a plurality of nozzles will often be used.

Drying gas is provided through conduit 5 and 10 drying gas disperser 6.

In the bottom of the drying chamber a fluidized layer 7 is maintained between the lowest part of the frusto-conical walls 2 and a cylindrical prolongation thereof. Below the fluidized layer 7 is a perforated plate 8 supplied with fluidizing and drying gas through conduit 9 and plenum 10.

In the top of the drying chamber, filter elements 11 are arranged in a circular pattern through which elements spent drying gas introduced through 6 and 10 20 and the vapour formed by the drying are withdrawn to a plenum 12 and exhausted through a duct 13.

The integrated filters have to be fairly flexible filters to secure that fines from the surface of the filters are just released and fall straight downwards when the filter blow-back cleaning is performed. This is not possible using fairly rigid filters as the fines release in all directions due to the higher blow-back pressure needed when the filter walls are not moving, as explained above. Such flexible filters are e.g. fabric filters, bag filters of a woven polymer material possibly supported by an inner metal basket, or non-woven felt filters. Such filter materials may be coated or not.

The materials to be spray dried by the process of the invention are all rather heat-sensitive. It is also

well-known in the art, that when using conventional methods especially the manufacture of highly agglomerated products involves a high risk for product failures such as grains. In spite of this, the process of the invention produces a highly agglomerated product with low grain rates, even when the inlet temperature of the drying gas introduced through 6 is between 160 and 400° C. A high drying gas inlet temperature is essential to achieve a good heat economy in the process, and, thus, the improved product qualities are obtained without increase of energy consumption as in certain prior art processes.

The flow of drying gas from 6 influences the flow path of the droplets ejected from the atomizer 4 as 15 schematically illustrated in the drawing.

(It is to be observed that the drawing has been made without regard to a possible swirling movement imparted by the disperser 6.)

When reaching the area shown hatched in the drawing, the flow of drying gas entraining moist particles formed by drying of the droplets has to turn outwards as schematically indicated. Thereby larger particles, including agglomerates, receive a movement towards the conical chamber walls 2 whereas the drying gas with entrained smaller particles moves upwards to the filter elements 11 This movement is supported by an upward gas stream, also entraining small particles, from the fluidized layer 7. When the gas passes through the filter elements, the entrained particles settle on the surface of the filter elements and form a layer thereon.

Sophisticated systems have been developed for releasing the particles from the surface of filter elements by counter-blowing, also termed back-blowing.

35 Reference is made to co-pending International Patent

Application PCT/DK99/00400 (Niro) describing a system for releasing the particles from the filter elements in a uniform, controlled manner creating an even flow of particles falling down on the conical walls 2 in an annular area which in the drawing is somewhat above the hatched area.

Having reached the conical walls, the particles form a layer sliding downwards in direction of the fluidized layer 7.

In contrast to conventional systems in which fine particles are re-introduced into the drying chamber by pneumatical means as described for instance in the above EP 729383, Niro, the particles sliding down the conical walls in the present process are not air-borne and thus form a denser, more compact particle layer with less distance between the individual particles.

When the particle layer sliding down the walls reaches the hatched area they meet the moist particles carried down into said area by the drying gas as explained above, but is not hit by wet droplets to any substantial extent. This means that excellent conditions exist for efficient agglomeration in said area and the high concentration of particles in the sliding layer efficiently protects the chamber walls against deposition of sticky particles.

The partly agglomerated particles then slide further down into the fluidized layer 7 for further drying and agglomeration. In the layer 7 also a certain classification takes place, and fine particles and dust 30 is blown off and agglomerated, some of them after having been separated from the gas by the filter elements 11 and released therefrom to fall down on the chamber wall and pass the hatched agglomeration area.

The products recovered from the layer 7 through 35 exit 14 are usually subjected to an after-treatment,

e.g. drying and cooling in a fluidized bed. If such an after-treatment creates a fraction of too fine particles, these may be re-introduced in the drying chamber for agglomeration as described in the copending International Patent Applications PCT/DK99/00511 and PCT/DK99/00512 (both to Niro).

It is essential that the positioning of the flexible filter elements 11 in the drying chamber and the release of fine particles therefrom is performed to ensure a uniform dispersion of the fine particles falling down on the conical wall above the annular horizontal area on the wall, i.e. the hatched area in the drawing, reached by the moist particles from the atomizer.

As it appears, the total process is performed without any re-wetting steps, including the conventional contact between fine particles and wet droplets near the atomizer, and this fact is reflected in the superior product qualities as explained above.

In the following, the invention is further illustrated by means of non-limiting embodiment examples and a comparison example.

Examples

The embodiment examples were performed in an integrated fluid bed dryer as the one shown in the drawing having internal flexible filters blowing back individually for particle release. The comparison example was performed in the same drying chamber but without internal filters. Instead fine particles were collected in a cyclone and recyled. Atomization was in all five examples made by means of a pressure nozzle. The conditions and results are summarized as follows:

Ī	Example	1	2	3	4	5
	Product	baby food	baby food	whole- milk	whole- milk	whole- milk
5	Feed composition, % w/w:					
10	Water Protein Fat Carbohydrates Ash	49.8 5.9 14.1 28.7 1.5	51.9 5.6 13.5 27.5 1.5	51.3 13.4 13.0 19.1 3.2	51.3 13.4 13.0 19.1 3.2	51.3 13.4 13.0 19.1 3.2
15	Feed, °C Feed, kg/h Feed pressure, barg	44 38.5 27	44 35.0 18	56 34.5 38	65 39.3 18	63 38.5 19
20	Main air inlet, kg/h Main air inlet, °C Air outlet, °C	445 194 66	545 180 74	550 185 76	550 180 69	550 182 70
25	IFB air inlet, kg/h IFB air inlet, °C Dust separation	251 59 internal filters	264 69 internal filters	249 60 internal filters	227 86 internal filters	240 84 cyclone
30	Filter air load, m3/h/m2 Filter ΔP, mm WG Cyclone ΔP, mm WG	175 37	208 34	186 37	193 36	150
	Powder: Moisture, %	3.27	2.07	2.42	3.77	3.51
35	Bulk density not tapped, g/ml Bulk density tapped	0.48	0.45	0.52	0.35	0.40
	100 times, g/ml	0.54	0.50	0.65	0.41	1.80
40	Free fat, %			0.69	0.66	1.80
	Particle size distri- bution:					
45	D (< 10%), μm	107	180	65	167	142
	D (< 50%), μm	285	371	154	464	410
	D (< 90%), μm	517	619	400	724	702
50	Grains	1-2	2	1	2-3	5-6

As it appears, the tests comprised two examples (1 and 2) drying baby food and three examples (3, 4 and 5) drying whole-milk. The Examples 1-4 illustrate the process of the present invention, using flexible internal filters, whereas Example 5 is a comparison example performed according to prior art using an external cyclone for separating fine particles from the spent drying gas, and reintroducing the particles into the drying chamber near the atomizing nozzle.

The baby food powder produced in Example 1 has a ${\rm D}_{50}$ value somewhat higher than what is found for the products presently marketed and at the same time the

rating for grains is at level with the ratings obtained when analyzing the best products in the market.

The baby food powder produced in Example 2 has a $\rm D_{50}$ value much larger than what can be found for 5 products presently marketed. At the same time, the rating for grains is only very little inferior. Normally, such a high $\rm D_{50}$ value is only obtained by conducting fine particles back into the area near the nozzle whereby the amount of grains is increased 10 corresponding to a rating of at least 4.

Examples 3 and 4 both produce whole-milk powder.

Example 3 produces a powder less agglomerated than the baby food powder of Example 1, and Example 4 produces a powder even more agglomerated than the coarse baby food powder produced in Example 2. The ratings for grains suited into the pattern for relation of the grains rate to the degree of agglomeration deducible from the Examples 1 and 2. The variation of the agglomeration rates was mainly achieved by operating the nozzle at different pressures.

The comparison Example 5 was performed using the same whole-milk concentrate starting material as in Examples 3 and 4, the internal filters were omitted, and the fine particles entrained in the spent drying gas were separated in an external cyclone and recycled to the nozzle area. The degree of agglomeration was nearly as high as in Example 4 but as far as grains is concerned the product was much inferior.

Further it appears from the table that for the 30 whole-milk powders produced in Examples 3 and 4 an unusually low value for free surface fat was obtained. The values were substantially lower than what was obtained in Comparison Example 5 indicating a more lenient treatment than the one in the Comparison 35 Example.

PATENT CLAIMS

- 1. A process for producing a spray dried baby food, whole-milk or skim-milk product, comprising the following steps:
- atomizing a liquid concentrate of baby food, whole-milk or skim-milk as droplets centrally into the upper part of a drying chamber of which at least the lower portion is defined by a downward tapering frustoconical wall;
- introducing drying gas at a temperature of 160-400° C downwards from the top of said chamber around the atomized droplets to partially dry these to moist particles and carry them in a downward widering direction;
- maintaining a fluidized particle bed at a temperature of 45-80° C in the bottom of the drying chamber and/or in a lower extension thereof, by means of an upward stream of fluidizing gas for drying, classifying and agglomeration of the particles therein;
- withdrawing a stream of gas comprising spent drying gas introduced at the top of the chamber and gas from said fluidized bed and at a temperature of 60-95° C from the chamber through flexible filter elements within said chamber, thereby settling fine particles having been entrained by said stream on the surface of the filter elements;

releasing the fine particles settled on the flexible filter elements by short, moderate counter blows to cause them to fall down on the frusto-conical wall at a location at level with or above a horizontal ring-shaped area on said wall where the largest concentration of said moist particles would have reached said wall if no fine particles from the filter elements had fallen down thereon, from which location said fine

particles slide downwards along the wall as a covering layer to reach said fluidized particle layer;

withdrawing an agglomerated product from the fluidized bed fulfilling one of the following three 5 combinations of agglomerate size distribution and grains rate (dertermined by the method of analysis described herein):

- (i): D_{10} (< 10%): 50-100 μ m, D_{50} (< 50%): 150-225 μ m, D_{90} (< 90%): 350-450 μ m and grains = 1;
 - (ii): D_{10} (< 10%): 100-200 μ m, D_{50} (< 50%): 225-400 μ m, D_{90} (< 90%): 450-600 μ m, and grains: above 1 but below or equal to 2;
- 15 (iii): D_{10} (< 10%): 200-300 μ m, D_{50} (< 50%): 400-600 μ m, D_{90} (< 90%): 600-900 μ m, and grains: above 2 but below or equal to 3.
- 2. The process of claims 1, wherein the positioning of said flexible filter elements in the drying chamber and the release of fine particles settled thereon is performed to obtain a uniform dispersion of the fine particles falling down on the conical wall above the ring-shaped horizontal area on the wall reached by the moist particles from the atomizer.
- 3. The process of anyone of the claims 1 and 2, wherein the liquid concentrate is atomized using a pressure nozzle ejecting droplets in a cloud forming a hollow downward widening cone which, influenced by the drying gas, is directed towards the conical wall of the drying chamber.
- 4. An agglomerated spray dried baby food, wholemilk or skim-milk product produced by the process of 35 claim 1 and fulfilling one of the following three


combinations of agglomerate size distribution and content of grains:

- (i): D_{10} (< 10%): 50-100 μ m, D_{50} (< 50%): 150-225 μ m, D_{90} (< 90%): 350-450 μ m and grains = 1;
 - (ii): D_{10} (< 10%): 100-200 μ m, D_{50} (< 50%): 225-400 μ m, D_{90} (< 90%): 450-600 μ m, and grains: above 1 but below or equal to 2;
- 10 (iii): D_{10} (< 10%): 200-300 μ m, D_{50} (< 50%): 400-600 μ m, D_{90} (< 90%): 600-900 μ m, and grains: above 2 but below or equal to 3.
- 5. An agglomerated spray dried baby food, wholemilk og skim-milk product having an agglomerate size distribution and content of grains: D $_{10}$ (< 10%): 100-200 μ m, D $_{50}$ (< 50%): 225-400 μ m, D $_{90}$ (< 90%): 450-600 μ m, and grains: above 1 but below or equal to 2.
- 6. An agglomerated spray dried baby food, whole-milk og skim-milk product having an agglomerate size distribution and content of grains: D $_{10}$ (< 10%): 200-300 μ m, D $_{50}$ (< 50%): 400-600 μ m, D $_{90}$ (< 90%): 600-900 μ m, and grains: above 2 but below or equal to 3.

ABSTRACT

Concentrates of baby food, whole-milk and skim-milk are spray dried to produce agglomerated powders having low 5 content of grains as defined herein. High-quality products are obtained by avoiding re-wetting process steps by using flexible internal filters delivering a compact flow of fine particles to the section in the lower portion of the spray dryer where the possibilities are optimal for contact with moist particles of suitable moisture content and the risk for contact with wet droplets and hot drying air is small.

15 (Fig. 1)



DECLARATION AND POWER OF ATTORNEY

As a below named inventor, I hereby declare that my residence, post office address and citizenship are as stated below next to my name: that I verily believe I am the original, first and sole inventor (if only one name is listed below) or a joint inventor (if plural names are listed below) of the subject matter claimed and for which a patent is sought in the application entitled:

"A PROCESS FOR PRODUCING A SPRAY DRIED, AGGLOMERATED POWDER OF BABY FOOD, WHOLE MILK OR SKIM MILK, AND SUCH POWDER"

	which application is:	Mannication Serial	No		
	the attached application for original application	🖾 application Serial No, and amended on			
t t v	hat I have reviewed and understand he claims, as amended by any amend which I am aware and which is mater claim foreign priority benefits under To patent or inventor's certificate listed b nventor's certificate on this invention	the contents of the specifi ment referred to above; th ial to the examination of th Itle 35, United States Cod elow and have also identi	at I acknowledge my duty to his application under 37 C.F.F. e §119, §172 or §365 of any fo fied on said list any foreign a	d application, including disclose information of a 1.56; and that I hereby breign application(s) for application for patent or	
	Application Number	Country	. Filing Date	Priority Claimed	
	$-\sqrt{2}$, , , , , , , , , , , , , , , , , , ,	
	thereby claim the benefit of Title 35, insofar as the subject matter of each capplication in the manner provided buty to disclose any material informapplication and the national or PCT in	of the claims of this applic by the first paragraph of T ation under 37 C.F.R. 1.56	itle 35, United States Code, which occurred between the	sted prior United States §112, I acknowledge my	
ē,	Application Serial No.	Filing Date	(patented, j	Status pending, abandoned)	
J			•	J	
s)	Robert J. Seas, Jr., Reg. No. 21,092; L. Reg. No. 24,513; J. Frank Osha, Reg. 19,093; Louis Gubinsky, Reg. No. 24,513; J. Frank Osha, Reg. No. 24,513; J. Frank Osha, Reg. No. 24,519; Howard L. Bernstein 31,333; Gordon Kit, Reg. No. 30,764; S. Reg. No. 32,197; William H. Mandir, F. 32,778, my attorneys to prosecute the connected therewith, and request the ZINN, MACPEAK & SEAS, 2100 Pen.	No. 24,625; Waddell A. Big 835; Neil B. Siegel, Reg. N. Jr., Reg. No. 26,577; Shelo , Reg. No. 25,665; Alan J. Housan J. Mack, Reg. No. 30, Reg. No. 32,156; Scott M. Da is application and to tran at all correspondence about ansylvania Avenue, N.W., I	o. 25,200; David J. Cushing, don I. Landsman, Reg. No. 2 (Asper, Reg. No. 25,426; Kenn 951; Frank L. Bernstein, Reg. aniels, Reg. No. 32,562; and Broact all business in the Pater the application be address (Vashington, D.C. 20037.	Reg. No. 28,703; John R. 5,430; Richard C. Turner, eth J. Burchfiel, Reg. No. No. 31,484; Mark Boland, ian W. Hannon, Reg. No. 1 and Trademark Officed to SUGHRUE, MION	
	I hereby declare that all statements information and belief are believed to willful false statements and the like states Title 18 of the United States Code an or any patent issuing thereon.	be true; and further that	fine or imprisonment, or bo	oth, under Section 1001 o	
	Date Nov- 4-99	First Inventor	Mourits Middle Initial	SØRENSEN Last Name	
	Residence VIRUM, Denmark	Signature / MM	mmu		
W	Residence DKX	Post Office Address 7 Skov	ridergårdsvej, DK-	2830 VIRUM	
·	Citizenship_Danish	Denma	<u> </u>		
Ju T	Date OCA 23-99 ALLERØD Residence SOBORG, Denmark	Second Inventor Ove First Name Signature	Hausee.	HANSEN Last Name	
	DKX	Post Office Address 22 Ra	345	Ox SØBORG. O ALLERØD	
	Citizenship Danish				

October 29, 1999 Third Inventor Martin Andreas Grønlund SCHOLTEN Middle Initial Last Name Residence RUNGSTED KYST, Denmark Signature ___ Post Office Address 6 Christiansgave, DK-2960 RUNGSTED KYST, Denmark Citizenship Denmark Fourth Inventor_ Date___ Middle Initial Last Name First Name Residence _____ Signature _____ Post Office Address Citizenship _____ Fifth Inventor_____ __Date_ Middle Initial Last Name Residence ____ Signature ___ Ų, Post Office Address W Citizenship Sixth Inventor_______First Name Date___ Middle Initial Last Name Residence Signature _____ Post Office Address Citizenship _____ Seventh Inventor Date Middle Initial Last Name First Name Signature _____ Residence _____ Post Office Address

Citizenship _____